

# KODAK

## USB-C Hub (6-IN-1&M.2)

### T344

### Specification





## KODAK USB-C Hub (6-IN-1&M.2) Model: T344

T344 is a multi-functional six in one+M.2 SSD hard drive case USB-C docking station, equipped with 3 USB3.1 10Gbps high-speed interfaces, 1 USB-C PD charging interface, 1 HDMI high-definition port, and an M.2 SSD adapter.

Mainly used as a USB-C interface for laptops, tablets, or mobile phones to solve the problem of insufficient interfaces and meet the interface requirements of users in different application scenarios such as business, office, learning, and entertainment.

High quality main control chips and converters are used internally, and the aluminum shell of the body is anodized in gray color. The surface is sandblasted with a delicate and durable feel, and has strong heat dissipation.

The wire is made of PVC material, which is soft, strong, and resistant to breakage. It uses multiple thick tinned copper cores inside, as well as multiple layers of shielding such as braided mesh and tin foil shielding layers. It has strong anti-interference ability, more stable transmission, and can be used under load for a long time.

## 1. Product specifications

- **Interface**
  - Input Port : Type-C 5V==3A(Max)
  - Output Port : USB 3.1X3 +Type C 3.0 PD +HDMI+M.2(NVME1.3)
- **USB-C PLUG**
  - Support Thunderbolt 3/4 , USB4,USB-C DATA;
- **USB3.1**
  - USB3.1: Support USB3.1 GEN2 10Gbps;
- **HDMI**
  - Support HDMI 2.0 3840\*2160 @ 60HZ,
  - Support both HDCP1.4 and HDCP2.3
- **M.2**
  - Support M.2 Socket 3 M-Key;
  - Support NVMe SSD, Support 10Gbps;
  - Support TYPE2242,2260,2280;
- **USB-C CHARGE**
  - Support PD3.0 100W
- **Size**
  - 128x47x14.3mm
- **Temperature Range**
  - Operation: 0°C ~ 70°C
  - Storage: -25°C ~ 85°C
- **Certification**
  - CE
  - FCC
  - RoHS
- **Operating System compatibility**
  - Support Windows XP and later version
  - Support MAC OS 10.8 and later version
  - Support IOS 14 and later version
  - Support Android 8 and later version



## 2. Product Performance

Output port	Transmission rate ( MAX)	Actual reference value
USB3.1 -A	10Gbps	write: >920MB/s Read: >960M B/s
M.2	10Gbps	write: >920MB/s Read: >960MB/s
USB3.0-Type C (charge)	PD3.0 100W	
HDMI	HDMI1.4 3840*2160 @ 30HZ	

## 3. Product design rendering





## 4. Product packaging

